

ELECTROLYTIC SINGLE REDUCED TINPLATE & TIN FREE PRODUCTS

Product Type	Form of Products	
	Coil	Cut to Length
Single Reduced Batch Annealing	TNB-TFB	TNBC-TFBC
Single Reduced Continuous Annealing	TNC-TFC	TNCC-TFCC

Steel Type	Steel Grades			
Single Reduced and Batch Annealed	TS230, TS245, TS260 TS275, TS290, TS340, T-1BA, T-2BA, T-3BA, T-4BA			
Single Reduced and Continuous Annealed	TH275, TH360, TH415, TH435, T-3CA, T-4CA, T-5CA		TH230, TH245, TH260	
Thickness (mm)	Width (mm)		Width (mm)	
	Minimum	Maximum	Minimum	Maximum
0,160 - 0,239	700	1100	700	1100
0,240 - 0,259	700	1169	700	1175
0,260 - 0,449	700	1235	700	1175
0,450 - 0,600	700	1255	700	1175

Subject:

- Thicknesses of 0,45 mm and above are subject to negotiation.
- TS230, TS340, TH245, TH260, TH340, TH360 grades are subject to negotiation.
- The Customer Technical Services should be contacted for technical questions not specified in the table.
- Minimum order length for cut to length is 450 mm and maximum 1200 mm.
- Lengths over 1200 mm are subject to negotiation.

ELECTROLYTIC DOUBLE REDUCED TINPLATE & TIN FREE PRODUCTS

Product Type	Form of Products	
	Coil	Cut to Length
Double Reduced Batch Annealed	DTNB-DTFB	DTNBC-DTFBC
Double Reduced Continuous Annealed	DTNC-DTFC	DTNCC-DTFCC

Steel Type	Form of Products			
Double Reduced	Batch Annealed		Continuous Annealed	
	TS520, TS550, DR-7.5BA, DR-8BA		TH520, TH550, TH580, TH620, TH520K, TH550K, DR-7.5CA, DR-8CA, DR-8.5CA, DR-9CA	
Thickness (mm)	Width (mm)			
	Minimum	Maximum	Minimum	Maximum
0,130 - 0,165	700	1100	700	1100
0,170 - 0,190	700	1169	700	1100
0,195 - 0,215	700	1235	700	1169
0,220 - 0,300	700	1235	700	1200

Subject:

- Lengths over 1200 mm are subject to negotiation.
- TH480 ve TS480 grades are subject to negotiation.
- The minimum order length for cut-to-length is 450 mm, maximum 1200 mm.
- The Customer Technical Services should be contacted for technical questions not specified in the table.